



BOSCH

Pn-Screwdriver - Ind.

180 WATT-SERIE | 0 607 453 431

Table of Content

| | |
|--------------------------|---|
| Spare parts list..... | 2 |
| Illustration - Type..... | 5 |

Spare parts list

| Item | Part Number | Description | | |
|-------------|--------------------|-------------------------|---------------------|-------|
| 1 | 3 605 108 177 | Motor Housing | BLUE | |
| 2 | 3 604 090 050 | Stator | 180W | |
| 3 | 3 604 220 104 | Rotor | | |
| 5 | 3 605 700 107 | Bearing Flange | | |
| 6 | 1 900 905 044 | groove ball bearing | 7x19x6 | |
| 7 | 3 605 700 148 | Bearing Flange | | |
| 8 | 1 900 905 028 | groove ball bearing | 7x17x5 | |
| 9 | 3 600 700 201 | Insert Pipe | | |
| 12 | 3 600 100 030 | Shim | | |
| 26 | 3 606 300 180 | Pinion | | |
| 27 | 3 600 101 047 | Stop Disc | | |
| 28 | 3 606 334 080 | Ring Gear | Z=42/54 | |
| 30 | 3 600 209 013 | Spacer Ring | BLACK | |
| 32 | 3 600 913 000 | Needle-Roller Assembly | INA K3x5x7 | |
| 34 | 3 600 700 060 | Intermediate housing | | |
| 35 | 1 903 201 042 | Needle Roller | DIN 5402-A3x11,8-G2 | |
| 38 | 3 606 337 193 | Planetary-Gear Carrier | | |
| 39 | 3 606 316 104 | Cylindrical Gear | | |
| 41 | 3 600 905 023 | groove ball bearing | | |
| 43 | 3 600 100 084 | Supporting Disc | | |
| 56 | 3 603 462 007 | Fitting | | |
| 57 | 3 600 206 005 | Sealing disk | | |
| 58 | 3 600 105 001 | Shim washer | | |
| 60 | 3 600 002 006 | Strainer | | |
| 61 | 3 603 462 000 | Silencer | | |
| 62 | 3 600 521 002 | Screening Ring | | |
| 63 | 3 603 201 070 | Straight Pin | L=62 MM | |
| 64 | 3 603 201 002 | Straight Pin | 35,3 MM | |
| 65 | 1 900 210 112 | O-Ring | 15x2 MM | |
| 66 | 3 603 201 009 | Straight Pin | | |
| 67 | 2 917 690 036 | Half-Length Grooved Pin | ISO 8741-2x10-ST | |
| 68 | 3 608 750 021 | Valve Cone | | |
| 69 | 2 917 550 088 | Straight Pin | DIN 6325-3M6x32 | |
| 73 | 3 600 210 122 | O-Ring | 25,0x2,0 MM | BLACK |
| 74 | 3 600 210 105 | O-Ring | 1,8x1,2 MM | |

Spare parts list

| Item | Part Number | Description |
|-------------|--------------------|-------------------------------------|
| 75 | 3 603 100 029 | Straight Pin |
| 76 | 3 602 033 005 | Push-Button |
| 77 | 3 604 610 016 | Compression Spring |
| 78 | 3 600 210 104 | O-Ring 16,0x1,0 MM |
| 79 | 3 600 313 011 | Screw Plug |
| 80 | 2 912 411 407 | Tapping Screw DIN 7982-ST2,9x16-F-Z |
| 81 | 3 608 750 045 | Housing |
| 82 | 3 602 000 002 | Changeover Lever |
| 83 | 3 604 619 017 | Compression Spring |
| 84 | 3 605 500 147 | Housing Cover BLUE |
| 85 | 3 600 921 002 | Guide Piece |
| 87 | 3 601 010 010 | Silencer |
| 88 | 3 603 231 007 | Valve Cone |
| 89 | 3 604 619 019 | Compression Spring |
| 95 | 1 601 11A 3HF | Nameplate |
| 96 | 3 601 119 136 | Manufacturer's nameplate |
| 99 | 3 601 110 572 | Sticker |
| 100 | 3 605 125 054 | Housing |
| 101 | 3 606 445 043 | Clutch Element |
| 102 | 3 603 124 022 | Output Shaft |
| 106 | 3 604 610 011 | Compression Spring |
| 107 | 3 604 615 004 | Compression Spring |
| 108 | 3 604 610 057 | Compression Spring |
| 109 | 3 604 619 003 | Compression Spring |
| 110 | 3 600 224 053 | Retaining ring |
| 113 | 3 600 499 023 | Clamp Bushing |
| 114 | 3 600 921 001 | Plain bearing |
| 115 | 3 601 023 011 | Sealing plate |
| 116 | 3 600 134 014 | Setting Ring |
| 117 | 1 600 101 023 | Plain Washer 0,5 MM THICK |
| 118 | 3 603 003 005 | Rod |
| 119 | 3 600 190 038 | Support Disc |
| 120 | 3 603 344 047 | Catch Disk |
| 121 | 3 604 710 063 | Straight Pin 17,75mm |
| 121 | 3 604 710 064 | Straight Pin 18,5mm |

Spare parts list

| Item | Part Number | Description |
|------|---------------|-----------------------------------|
| 121 | 3 604 710 065 | Straight Pin 18mm |
| 124 | 3 600 250 004 | Ring |
| 125 | 3 600 202 020 | Backup ring |
| 126 | 3 600 224 006 | Retaining ring |
| 127 | 1 903 230 006 | Ball DIN 5401-3,5 MM-III-ST |
| 128 | 1 903 230 008 | Ball 4,5 MM III DIN 5401-ST |
| 129 | 1 903 230 003 | Ball DIN 5401-2,5MM-III-ST |
| 133 | 3 600 190 024 | Washer |
| 135 | 3 600 224 059 | Retaining ring |
| 136 | 2 600 101 513 | Plain Washer |
| 140 | 2 916 080 012 | Locking Washer DIN 6799-9-FSt |
| 141 | 3 600 400 022 | Protection Sleeve |
| 143 | 3 600 210 038 | O-Ring 9,0x1,2 MM |
| 144 | 1 903 230 002 | Ball 2 MM III DIN 5401 ST |
| 145 | 3 600 210 116 | O-Ring |
| 652 | 3 603 386 066 | Hose fitting |
| 654 | 3 601 923 019 | Suspension Loop |
| 657 | 3 607 950 027 | Screwdriver |
| 706 | 3 604 618 003 | Compression Spring WHITE |
| 801 | 3 607 031 500 | Cutoff Coupling Sp Set |
| 802 | 3 607 031 504 | Assembly Of Service Parts |
| 804 | 3 607 031 304 | Assembly Of Service Parts 5 PIECE |
| 806 | 3 609 202 745 | Screw Plug |
| 868 | 3 608 750 042 | Valve Cone |
| 876 | 3 607 030 332 | Assembly Of Service Parts |
| 888 | 3 607 031 503 | Assembly Of Service Parts |

Illustration - Type - E

0 607 453 431; 432
 Issue | 12-10-25
 Stand | **Fig./Abb. 1**

◆ Assemble pos. 101 and pos. 102;
 now place in pos. 127 (10 ball bearings)!
 Pos. 101 und Pos. 102 zusammenfügen;
 danach 10 Kugeln Pos. 127 einfüllen!

