

2743-20, 15 Ga. Angled Finishing Nailer Magazine Attachment

FIG.	PART NO.	DESCRIPTION OF PART	NO. REQ.
1	44-34-0005	Rear Upper Receiver, 15 Ga. Angled	1
2	44-60-1122	Step Connecting Pin	1
3	06-82-1087	M3.0 x 12mm Pan Hd. ST T-10 Screw	2
4	-----	Latch Plate	1
5	-----	Release Latch	1
6	42-36-0205	Release Bracket	1
7	44-60-1123	Latch Pin	2
8	42-09-0295	Release Bracket Pivot Arm	1
9	44-60-1124	Catch Pin	1
10	44-34-0006	Front Upper Receiver, 15 Ga. Angled	1
11	42-38-0141	No-Mar Pad	1
12	44-94-0202	Work Contact Rod	1
13	44-34-0007	Feed Lip, 15 Ga. Angled	1
14	-----	Depth Adjustment Wheel	1
15	-----	External Retaining Ring	1
16	-----	C-Ring	1
20	40-50-1841	Depth Adjustment Spring	1
23	05-81-0166	M4.0 x 0.7 x 7mm Pan Hd. T-20 Screw	1
28	40-50-1843	Constant Force Spring	1
35	44-81-0045	Magazine Channel, 15 Ga. Angled	1
40	34-60-2493	External Retaining Ring	1
41	44-96-0310	Magazine Roller	1
42	05-81-0708	M5 x 0.8 x15mm T-25 Screw	1
50	45-24-0375	Magazine Pusher Assembly	1
51	44-52-0010	No-Mar Pad/Rod Assembly	1
52	44-34-0008	Rear Upper Receiver Assembly, 15 Ga. Angled	1
53	44-14-0305	Depth Adjustment Assembly	1
55	43-40-0901	Magazine Assy. for 9.0Ah batteries or smaller	1
55	43-40-0902	Magazine Assy. for 12.0Ah batteries or smaller	1
56	44-20-0176	Release Latch Assembly	1
57	45-94-0304	Depth Adjustment Wheel Kit	1
74	06-82-3065	M5 x 0.8 Pan Hd. T-25 Machine Screw	1
84	48-55-3510	Contractor Bag	1

NOTE:

The initial Magazine design on model 2743-20 allows the tool to operate off of several different M18 REDLITHIUM™ battery sizes from a 1.5 amp-hours up to 9.0 amp-hours.

To power an earlier version of the 2743-20 with a 48-11-1812 M18™ REDLITHIUM™ 12.0 amp-hour battery, Magazine Assembly 43-40-0902 must be ordered and installed.

See the detail below to determine what magazine assembly is on your tool.

